

## INO404X-RAWT

### Premium Series WDR Outdoor Mini PTZ Dome Camera with Smart IR

Infinique offers a wide range of IP based high definition cameras available in various housing formats, including Box, Dome and Bullet. Our cameras are equipped with superior image sensor and digital signal processor to produce sharp, crisp pictures and are enclosed in weather and vandal resistant housings making it suitable for use in all security applications. The ONVIF compliance of the cameras helps in easy integration, providing peace of mind for your investment. From small to very large installations, Infinique's cameras are reliable, future proof and an ideal solution for your video surveillance needs.

Infinique's 4MP IR PTZ comes with 4X Optical Zoom with 130dB true WDR. It is compact in size with a reliable mechanical design that offers precise positioning and predictable high-speed tracking. This high quality PTZ dome provides excellent image quality in difficult lighting conditions and provides features such as privacy zone blanking, guard tours, multiple presets, alarms which are required for efficient 24/7 surveillance.

This camera is equipped with smart IR and has a night vision of up to 20m and provides a very high speed continuous 350° degree rotation at up to 54° per second.


An easy to install design with wall, ceiling and pole mount brackets allows for quick installation, makes it a suitable choice for any indoor and outdoor application such as large retail stores, malls, airports, factories, warehouses, airports, government buildings where detailed video surveillance is essential.

### Product Features

- 1/1.8" Progressive Scan CMOS
- 4MP Resolution at 50/60 fps
- Smart IR, IR Distance 20m
- 130dB True WDR
- 4x Optical Zoom
- H.265+, H.265, H.264 Compression
- Up to 3 Simultaneous Video Streams
- Track targets with 350° Rotation
- Preset/Tour/Scan/Pattern Function
- True Day & Night with ICR Cut Filter
- S/N Ratio of more than 50dB
- Micro SD Card Slot for Onboard Storage
- Audio I/O
- Metal Housing
- IP66 and IK10 Rated
- Easy control by Keyboard (OSD)
- ONVIF Compliant




### Dimensions



### Accessories



Part No: IJBDCM-150  
Ceiling Mount Junction  
Box



Part No: IBKTCM  
Ceiling Mount Bracket



Part No: IBBCPM  
Pole Mount Bracket



Part No: IBDLWM-2  
Wall Mount L Bracket



Part No: IBCRWM  
Corner Mount Bracket

# INO404X-RAWT

Premium Series WDR Outdoor Mini PTZ Dome Camera with Smart IR



IMAGE PERFORMANCE		NETWORK	
Image Sensor	1/1.8" Progressive Scan CMOS	Network Port	10/100M BASE-TX, RJ-45 Connector
Resolution (H x V)	2560x1440	Cabling Type	Category 6 and higher
Minimum Illumination	Color: 0.001 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR	Network Protocol	IPv4/IPv6, HTTP, HTTPS, FTP, SMTP, UPnP, SNMP, DNS,
Image Rate (FPS)	50 / 60	ONVIF Protocol	Onvif ( Profile S, Profile G, Profile T), Http API
IR Distance (m)	20	Security	Password protection, complicated password, HTTPS encryption, IP address filter, control timeout settings
IR Dimming	Adjustable	Users	5 Users
S/N Ratio	More than 50dB	PC Web Browser	IE10/11, Edge V.79 above, Chrome V.57 above
<b>LENS</b>		Mobile Device	Android, iPhone
Focal Length (mm)	2.8 mm to 12 mm	Events	Motion detection
Iris	Auto, Manual	Event Handlers	Upload to FTP, E-mail, Audible Warning, Flashing Lights, SD Card Recording
Aperture Ratio	Max. F1.3	<b>PTZ CONTROL</b>	
Angle of View (deg)	H: Wide 114.6~ Tele 48.3 V: Wide 59~Tele 27.1	Pan/Tilt Angle (deg)	Pan: 350/ Tilt: 0° to 80°
Zoom Ratio	4x Optical Zoom	Pan Speed (deg)	Configurable from 0.6° to 54°/s
<b>VIDEO AND AUDIO</b>		Tilt Speed (deg)	Configurable from 0.6° to 52°/s
Video Compression	H.265+, H.265 Main Profile H.264+, H.264 Baseline Profile/Main Profile/High Profile	Pre-set Speed / Positions	255 deg per sec
Main Stream	2560x1440, 2304x1296, 1920 x 1080, 1280 x 720	Tour	NA
Sub Stream	1280x720, 640 x 480, 320x240	Scan	NA
Mobile Stream	340x480, 320x240	Pattern	NA
Electronic Shutter Control	1/5 s to 1/20000 s	Default Position	NA
Day/Night Control	IR Cut Filter	Communication	NA
Flicker Control	50 Hz, 60 Hz	RS-485 Protocol	NA
True WDR	130dB	<b>MECHANICAL</b>	
White Balance	Auto / Manual / Indoor	Housing ID	V4POMWH671020S1
Backlight Compensation	On / Off	Dimensions (mm)	153 (D) x 121.3 (H)
Automatic Gain Control	Auto/Manual, Adjustable Level	Weight (g)	950
Smart Defog	NA	Finish	White Powder Coat, RAL 9003
Audio Compression	G.711a/G.711u	Installation	Ceiling / Wall / Pole Mount
Audio Input / Output	Built in Microphone and Speaker	<b>ELECTRICAL</b>	
Video Output	IP-RJ45, CVBS-BNC Type	Power Consumption	9W
Alarm I/O	NA	Power Source	PoE IEEE802.3af; DC12V
Video Bit rate	8 kbps to 8192 kbps	Power Connector	2 pin terminal block
OSD	Camera ID, Pan/Tilt Angle, Mode, Zoom Ratio Setting/ Control via Joystick	RTC Backup Battery	3V Magnesium Lithium
Image Orientation	Image Flip, Mirror	<b>ENVIRONMENTAL</b>	
Image Controls	Brightness, Contrast, Hue, Saturation, Acu, Gamma	Operating Temperature (C)	-30 to 60
Advanced Functions	Motion Detection Image Rotation, Anti-Fog, Smart IR Detection	Storage Temperature (C)	-20 to 60
<b>VIDEO ANALYTICS</b>		Operating Humidity	0% - 90% non condensing
Advance Video Analytics	Face Recognition, Human & Vehicle, Perimeter Intrusion, Line Crossing, Stationary Object, Crossing Counting, Heat Map, Crowd Density, Queue Length, License Plate Detection	Ingress Protection Rating	IP66
<b>LOCAL STORAGE</b>		Impact Rating	IK10
Memory Card Slot	Micro SD/SDHC/SDXC, Max 512GB	<b>STANDARDS COMPLIANCE</b>	
Recording	Video and Image; Auto / Manual; Motion, Alarm Trigger, Schedule	Emissions	FCC Part 15 Subpart B Class B EN 55022:2010, IC ICES-003 Class B
<b>ORDERING INFORMATION</b>		Immunity	EN 55024:2010
<b>PART NUMBER</b>	<b>DESCRIPTION</b>		
INO404X-RAWT	Infonique Premium Series Outdoor IR Mini PTZ Dome IP Camera, 1/1.8 CMOS Sensor, 4MP, 4X Optical Zoom, H.265, H.264, Three Stream, 130dB WDR, True Day and Night with ICR, Adjustable Bit Rate, ONVIF Compliant, Audio, SDHC Slot, IP66, IK10		
IBDLWM-2	Infonique Camera L Bracket, Wall Mount Base Diameter 163 mm		
IBKTCM	Infonique Pendant Mount Ceiling Bracket, 45 (D) x 294 (H) mm		
IBBCPM	Infonique Pole Mount Bracket with Metal Ties, 125 (L) x 46 (W) x 200 (H) mm		
IJBDCM-150	Infonique Ceiling Mount Junction Box, Base Diameter 150 mm		
IBCRWM	Infonique Corner Mount Bracket, 200 (L) x 130 (W) x 172.8 (D) mm		

# INO404X-RAWT

Premium Series WDR Outdoor Mini PTZ Dome Camera with Smart IR



## Housing Accessories

### WALL MOUNT APPLICATION



L Bracket  
IBDLWM-2

### CEILING MOUNT APPLICATION



Junction Box  
IJBDCM-150

### POLE MOUNT APPLICATION



Pole Bracket  
IBBCPM

### CEILING MOUNT APPLICATION



Ceiling Bracket  
IBKTCM



Junction Box  
IJBDCM-150



Junction Box  
IJBDCM-150

### CORNER MOUNT APPLICATION



Corner Bracket  
IBCRWM



L Bracket  
IBDLWM-2



Infinique, a Canadian company is a manufacturer of high performing end-to-end solutions in copper, fiber and video surveillance systems. For more information visit our website at [www.infinique.com](http://www.infinique.com) or email us at [sales@infinique.com](mailto:sales@infinique.com).